

SUDONG

BRUSHLESS SCREWDRIVER with 2 years warranty

0.01Nm~15Nm



SUDONG

www.sudong.eu

English version

● SD-30V40W3P



● SD-30V40W6P



● SD-30V60W3P



● SD-36V200W3P






● SD-36V120W3P



● SD-30V75W-8P-BC



Dimensions



Features

- The size is small so that workplace looks beautiful and neat in which only a little space is required.
- The design is two-stage speed to improve assembly efficiency and quality.
- More convenient as the direct input AC power is used. The output voltage is stable and effective to improve the lock quality.

Technical parameters

MODEL	SD-30V40W3P	SD-30V40W6P	SD-30V60W3P	SD-30V75W-8P-BC	SD-36V120W3P	SD-36V200W3P
Input voltage	AC 110V-AC 260V					
Output voltage	DC 24V/DC 30V			DC 36V		
Output power	40W		60W	75W	120W	200W
Rated current	1.35A		2A	2.5A	3.3A	3.5A
Weight (g)	135		292	420	500	635
Dimension (mm)	115x51x32		139x68x38	159x88x45	176x89x42	210x80x52
Output terminal	3PIN	6PIN	3PIN	8PIN	3PIN	

Z Adapter

Application

- SDZ-1
- SDZ-2



- SD-DA1000L



- SDZ-1

90° Adapter

- SDL-1A
- SDL-2A
- SDL-3A



- SDL-1
- SDL-2



Application

- SD-BC7000L

- SDL-2A



- SD-BC5000L

- SDL-1A



- SD-A8500L

- SDL-3A



- SD-A500L

- SDL-1



- Applicable to assembly operations that cannot be directly manipulated to meet the special lock-pay requirements.

- Special type can be customized.

MODEL	Suitable for electric screwdriver Type
SDL-1A	SD-BC4500L SD-BC4500LF SD-BC5000L SD-BC5000LF SD-BC5500L SD-BC5500LF SD-BA4500L SD-BA4500LF SD-BA5000L SD-BA5000LF SD-BA5500L SD-BA5500LF
SDL-2A	SD-BC6000L SD-BC6300L SD-BC7000L SD-BA6000L SD-BA6300L SD-BA7000L
SDL-3A	SD-CA7500L SD-CA8000L SD-CA8500L SD-A7500L SD-A8000L SD-A8500L
SDL-1	SD-A1010L SD-A2015L SD-A3019L SD-A450L SD-A450LF SD-A500L SD-A500LF SD-A550L SD-A550LF SD-A4500L SD-A4500LF SD-A5000L SD-A5000LF SD-A5500L SD-A5500LF
SDL-2	SD-A600L SD-A630L SD-A700L SD-A6000L SD-A6300L SD-A7000L

Spring Balancer



SD-1

Technical parameters

Type	Load weight	Stretching length	Weight
SD-1	0.5-1.5Kg	1.5M	0.4Kg

Features

- Reduce the weights receive on a hand by hanging over a screwdriver, easy operation.
- Adjustable operating height, automatic returning to position after use, avoids breaking or bending by long-term using for Electric Screwdriver Power Cord.

Application



Accessory for suction driver

Accessory for suction driver



SD-Q1



SD-Q2



SD-Q3

Features

- For the magnetic force of the screw can not be or automated machine assembly operations.
- Suitable for SUDONG full range of electric screwdrivers.
- Special models can be customized.

Application



Power cord

- Straight power cord



SD-3P



SD-8P



SD-6P

Features


- New materials and difficult to break, super durable.
- Suitable for normal/intelligent/auto machine range of brushless electric screwdriver.

MODEL	A	B	C	
Straight	1.6M	2.0M	3.0M	Special lengths can be customized.

Signal controller



Application



Gun-type handle



Application



Features

- Best suited for transverse tightening screw operation.
- The tightening torque can effectively reduce the recoil and make the operation safer.

Torque protective sleeve



Features

- Can effectively prevent the operator free to adjust the torque.

Application



Electric screwdriver socket

TYPE

- SD-K1
- SD-K2
- SD-K3

Features

- Easy to install in the table which could not hanging possible.



Screwdriver head specifications table					
Style	Specification				L
	Back-end model	Size			
<p>+</p> <p>Cross-head screwdriver</p>		d	P	e	40-200
		2.0-2.6	00	20-30	
		3.0-5.0	1 2		
<p>A font screwdriver head</p>		W			40-100
		2.0-3.0	0.4		
		3.0-4.0	0.6		
<p>Hexagon head screwdriver</p>	<p>A: 5mm Hex B: 1/4" Hex C: 4mm\varnothing D: 5mm\varnothing</p>	H			40-100
		1.27 / 1.5 / 2.0			
		2.5 / 3.0 / 4.0 5.0 / 6.0			
<p>Hex socket</p>		A/F			50-150
		2.2-14.0			
<p>Plum-type screwdriver head</p>		d	T		40-100
		2.0	T5 - T6		
		2.5	T7 - T8		
		3.0	T9 - T10		
		3.5	T15		
		4.0	T20		
		5.0	T25		
6.0	T30				
<p>Double-headed cross-shaped screwdriver head</p>	<p>A: 5mm Hex B: 1/4" Hex</p>	P			45-300
		1			
		2			

Type choreography description:

A-L-d-e-P

- : Back-end Type: A: 5mm HEX B: 1/4" HEX C: \varnothing 4mm D: \varnothing 5mm
- : Front-end length
- : Front-end diameter D
- : The total length of L
- : (00, 0, 1, 2, 0.4, T5, ...) Output specifications

SUDONG



SUDONG

Industrial Electrical Screwdrivers and accessories



+36-30/381-1185



RÉVÉSZ
www.reveszbt.hu

**DISTRIBUTION
and SERVICE:**



Révész Industrial and Trading Ltd.
2600 Vác, Balassagyarmati út 42.
Tel./fax: 27-305-737